

# 6 SERIES



6120 - 6130 - 6140 Powershift  
6120 - 6130 - 6140 TTV



6 Series Agrotрон		6120 Powershift	6130 Powershift	6140 Powershift
<b>ENGINE</b>				
Model		FARMotion	FARMotion	FARMotion
Cylinders/Displacement	No./cc	4/3849	4/3849	4/3849
Bore/Stroke	mm	103/115.5	103/115.5	103/115.5
Turbo intercooler	Type	●	●	●
Common Rail Injection 2000 bar	Type	●	●	●
Maximum power 2000 rpm	kW/hp	85/116	93/126	100/136
Rated power 2200 rpm	kW/hp	80.6/110	88.2/120	94.9/129
Max. torque 1600 rpm	Nm	462	506	544
Torque backup	%	32%	30%	28%
Viscostatic fan		●	●	-
Electronic viscstastic fan		○	○	●
Hydraulic Engine Braking (HEB)		○	○	○
Diesel fuel tank	l	200	200	200
<b>POWERSHIFT TRANSMISSION</b>				
Manufacturer		SDF	SDF	SDF
Model		T5430	T5450	T5450
Electro-hydraulic reverse shuttle Powershuttle with 5 adjustable settings		●	●	●
5-speed gearbox with triple Powershift speeds		●	●	●
Number of speeds	FW+RV	30+30	30+30	30+30
Number of speeds with underdrive and supercreeper gear	FW+RV	60+60	60+60	60+60
Max. speed	km/h	50 (40 with reduced engine speed)	50 (40 with reduced engine speed)	50 (40 with reduced engine speed)
Stop&Go system		●	●	●
Hydraulic parking brake		●	●	●
Electro-hydraulic four-wheel activation		●	●	●
Electro-hydraulic differential lock activation, front and rear		●	●	●
ASM system		-	●	●
Front axle		SDF 2	SDF 2.5	SDF 2.5
Front axle suspension		○	○	○
Rear PTO 540/540 ECO/1000/1000 ECO		●	●	●
Front PTO 1000		○	○	○
<b>HYDRAULIC SYSTEM</b>				
Delivery rate	l/min	90 open centre/120 LS	90 open centre/120 LS	90 open centre/120 LS
Auxiliary control units at rear	n°	3/4 mechanical 4/5 electro-hydraulic	3/4 mechanical 4/5 electro-hydraulic	3/4 mechanical 4/5 electro-hydraulic
Electronically controlled rear hitch (EHR)		●	●	●
Lifting capacity of rear hitch	kg	5000 7000 with additional lifting cylinder	5000 7000 with additional lifting cylinder	7000
Rear hitch category		II / III	II / III	II / III
Front linkage		○	○	○
Lifting capacity of front linkage	kg	2880	2880	2880
Pneumatic trailer braking system		○	○	○
Front loader Light and Ready Kit		○	○	○
Hydraulic trailer brake valve		○	○	○
<b>CAB</b>				
Cab suspension		Hydro Silent-Block/mechanical/ pneumatic	Hydro Silent-Block/mechanical/ pneumatic	Hydro Silent-Block/mechanical/ pneumatic
Instrument panel		InfoCentre <sup>Pro</sup>	InfoCentre <sup>Pro</sup>	InfoCentre <sup>Pro</sup>
8" iMonitor		○	○	○
Driver's seat		Mechanical/Pneumatic	Mechanical/Pneumatic	Mechanical/Pneumatic
Air conditioning		○	○	○
Panoramic sunroof		○	○	○
FOPS sunroof		○	○	○
LED working headlights		○	○	○
SDD steering system		○	○	○
<b>DIMENSIONS AND WEIGHTS</b>				
Wheelbase	mm	2540	2550	2550
Length	mm	4428	4428	4428
Height (centre of rear axle to roof)	mm	2025	2025	2025
Maximum permitted total weight	kg	8000	9000	9000

● = standard ○ = optional - = Not available

\* : depending on standard or optional equipment



6 Series Agrotрон		6120 TTV	6130 TTV	6140 TTV
<b>ENGINE</b>				
Model		FARMotion	FARMotion	FARMotion
Cylinders/Displacement	No./cc	4/3849	4/3849	4/3849
Bore/Stroke	mm	103/115.5	103/115.5	103/115.5
Turbo intercooler	Type	●	●	●
Common Rail Injection 2000 bar	Type	●	●	●
Maximum power 2000 rpm	kW/hp	85/116	93/126	100/136
Rated power 2200 rpm	kW/hp	80.6/110	88.2/120	94.9/129
Max. torque 1600 rpm	Nm	462	506	544
Torque backup	%	32%	30%	28%
Viscostatic fan		●	●	-
Electronic viscostatic fan		○	○	●
Hydraulic Engine Braking (HEB)		○	○	○
Diesel fuel tank	l	200	200	200
<b>POWERSHIFT TRANSMISSION</b>				
Manufacturer		SDF	SDF	SDF
Model		T5431 CVT	T5451 CVT	T5451 CVT
Electro-hydraulic reverse shuttle Powershuttle with 5 adjustable settings		●	●	●
Speed ranges	n°	2 (field/transport) electro-hydraulic controls	2 (field/transport) electro-hydraulic controls	2 (field/transport) electro-hydraulic controls
Max. speed	km/h	50 (40 with reduced engine speed)	50 (40 with reduced engine speed)	50 (40 with reduced engine speed)
PowerZero system		●	●	●
Hydraulic parking brake		●	●	●
Electro-hydraulic four-wheel activation		●	●	●
Electro-hydraulic differential lock activation, front and rear		●	●	●
ASM system		●	●	●
Front axle		SDF 2	SDF 2.5	SDF 2.5
Front axle suspension		○	○	○
Rear PTO 540/540 ECO/1000		●	●	●
Front PTO 1000		○	○	○
<b>HYDRAULICS SYSTEM</b>				
Delivery rate	l/min	90 open centre/120 LS	90 open centre/120 LS	90 open centre/120 LS
Auxiliary control units at rear	n°	3/4 mechanical 4/5 electro-hydraulic	3/4 mechanical 4/5 electro-hydraulic	3/4 mechanical 4/5 electro-hydraulic
Electronically controlled rear hitch (EHR)		●	●	●
Lifting capacity of rear hitch	kg	5000 7000 with additional lifting cylinder	5000 7000 with additional lifting cylinder	7000
Rear hitch category		II / III	II / III	II / III
Front linkage		○	○	○
Lifting capacity of front linkage	kg	2880	2880	2880
Pneumatic trailer braking system		○	○	○
Front loader Light and Ready Kit		○	○	○
Hydraulic trailer brake valve		○	○	○
<b>CAB</b>				
Cab suspension		Hydro Silent-Blocks/mechanical/ pneumatic	Hydro Silent-Blocks/mechanical/ pneumatic	Hydro Silent-Blocks/mechanical/ pneumatic
Instrument panel		InfoCentre <sup>Pro</sup>	InfoCentre <sup>Pro</sup>	InfoCentre <sup>Pro</sup>
8" iMonitor		○	○	○
Driver's seat		Mechanical/Pneumatic	Mechanical/Pneumatic	Mechanical/Pneumatic
Air conditioning		○	○	○
Panoramic sunroof		○	○	○
FOPS sunroof		○	○	○
LED working headlights		○	○	○
SDD steering system		○	○	○
<b>DIMENSIONS AND WEIGHTS</b>				
Wheelbase	mm	2540	2550	2550
Length	mm	4428	4428	4428
Height (centre of rear axle to roof)	mm	2025	2025	2025
Maximum permitted total weight	kg	8000	9000	9000

● = standard ○ = optional – = Not available


\* : depending on standard or optional equipment

Technical data and images are provided for guidance only. DEUTZ-FAHR makes every effort to tailor its products more closely in line with your needs and therefore reserves the right to make updates at any time and without prior notice.

Marketing-Communication Service – Code 308.8182.4-0 – 02/20

DEALER

To discover more please contact your dealer  
or visit [deutz-fahr.com](http://deutz-fahr.com).

DEUTZ-FAHR is a brand of  SDF

